



LED

Pila Luminaires brochure



Specifications - PILA WL007C LED14S/740 PSU OVL WH

Benefits

- Energy saving
- Robust luminaire
- Reliable quality



Product description	PILA WL007C LED14S/740 PSU OVL WH
Light output (lm)	1400
Power (W)	15
CCT (K)	4000
Mains voltage	220-240V / 50-60Hz
Lifetime	20,000 hrs L70B50
CRI	70
Connection	Screw terminal
IP rating	IP65 / IP54 (MDU version)
Power factor	> 0.9
Safety class	Class II
Housing material	Polycarbonate
Color	White
EOC	8710163335100

Specifications - PILA WL007C LED13S/740 PSU RND MDU WH

Benefits

- Energy saving
- Robust luminaire
- Reliable quality



Product description	PILA WL007C LED14S/740 PSU OVL WH
Light output (lm)	1300
Power (W)	15
CCT (K)	4000
Mains voltage	220-240V / 50-60Hz
Lifetime	20,000 hrs L70B50
CRI	70
Connection	Screw terminal
IP rating	IP65 / IP54 (MDU version)
Power factor	> 0.9
Safety class	Class II
Housing material	Polycarbonate
Color	White
EOC	8710163335117

Specifications - PILA BN007C LED32S/840 PSU L1200

Benefits

- Energy saving
- Robust luminaire
- Reliable quality



Product description	PILA BN007C LED32S/840 PSU L1200
Light output (lm)	3200
Power (W)	32
CCT (K)	4000
Mains voltage	220-240V / 50-60Hz
Lifetime	20,000 hrs L70B50
CRI	80
Connection	Fly wire 0.15m
IP rating	IP20
Power factor	> 0.9
Safety class	Class I
Housing material	Polycarbonate/steel
Color	White
EOC	8710163335087

Specifications - PILA BVP007 10W 4000k

Benefits

- Energy saving
- Robust luminaire
- Reliable quality



Product description	PILA BVP007 10W 4000k
Light output (lm)	850
Power (W)	10
CCT (K)	4000
Mains voltage	220-240V / 50-60Hz
Lifetime	20,000 hrs L70B50
CRI	70
Connection	Flying wire
IP rating	IP65 / IK08
Power factor	> 0.9
Safety class	Class I
Housing material	Polycarbonate/steel
Color	White
EOC	8710163329871

Specifications - PILA BVP007 20W 4000k

Benefits

- Energy saving
- Robust luminaire
- Reliable quality



Product description	PILA BVP007 20W 4000k
Light output (lm)	1700
Power (W)	20
CCT (K)	4000
Mains voltage	220-240V / 50-60Hz
Lifetime	20,000 hrs L70B50
CRI	70
Connection	Flying wire
IP rating	IP65 / IK08
Power factor	> 0.9
Safety class	Class I
Housing material	Polycarbonate/steel
Color	White
EOC	8710163329888

Specifications - PILA BVP007 50W 4000k

Benefits

- Energy saving
- Robust luminaire
- Reliable quality



Product description	PILA BVP007 50W 4000k
Light output (lm)	4250
Power (W)	50
CCT (K)	4000
Mains voltage	220-240V / 50-60Hz
Lifetime	20,000 hrs L70B50
CRI	70
Connection	Flying wire
IP rating	IP65 / IK08
Power factor	> 0.9
Safety class	Class I
Housing material	Polycarbonate/steel
Color	White
EOC	8710163329895

Specifications - PILA BVP007 10W 3000k

Benefits

- Energy saving
- Robust luminaire
- Reliable quality



Product description	PILA BVP007 10W 3000k
Light output (lm)	850
Power (W)	10
CCT (K)	3000
Mains voltage	220-240V / 50-60Hz
Lifetime	20,000 hrs L70B50
CRI	70
Connection	Flying wire
IP rating	IP65 / IK08
Power factor	> 0.9
Safety class	Class I
Housing material	Polycarbonate/steel
Color	White
EOC	8710163329901

Specifications - PILA BVP007 20W 3000k

Benefits

- Energy saving
- Robust luminaire
- Reliable quality



Product description	PILA BVP007 20W 3000k
Light output (lm)	1700
Power (W)	20
CCT (K)	3000
Mains voltage	220-240V / 50-60Hz
Lifetime	20,000 hrs L70B50
CRI	70
Connection	Flying wire
IP rating	IP65 / IK08
Power factor	> 0.9
Safety class	Class I
Housing material	Polycarbonate/steel
Color	White
EOC	8710163329918

Specifications - PILA BVP007 50W 3000k

Benefits

- Energy saving
- Robust luminaire
- Reliable quality



Product description	PILA BVP007 50W 3000k
Light output (lm)	4250
Power (W)	50
CCT (K)	3000
Mains voltage	220-240V / 50-60Hz
Lifetime	20,000 hrs L70B50
CRI	70
Connection	Flying wire
IP rating	IP65 / IK08
Power factor	> 0.9
Safety class	Class I
Housing material	Polycarbonate/steel
Color	White
EOC	8710163329925

Specifications - PILA BVP007 10W 4000k MDU

Benefits

- Energy saving
- Robust luminaire
- Reliable quality



Product description	PILA BVP007 10W 4000k MDU
Light output (lm)	850
Power (W)	10
CCT (K)	4000
Mains voltage	220-240V / 50-60Hz
Lifetime	20,000 hrs L70B50
CRI	70
Connection	Flying wire
IP rating	IP65 / IK08
Power factor	> 0.9
Safety class	Class I
Housing material	Polycarbonate/steel
Color	White
EOC	8710163329932

Specifications - PILA BVP007 20W 4000k MDU

Benefits

- Energy saving
- Robust luminaire
- Reliable quality



Product description	PILA BVP007 20W 4000k MDU
Light output (lm)	1700
Power (W)	20
CCT (K)	4000
Mains voltage	220-240V / 50-60Hz
Lifetime	20,000 hrs L70B50
CRI	70
Connection	Flying wire
IP rating	IP65 / IK08
Power factor	> 0.9
Safety class	Class I
Housing material	Polycarbonate/steel
Color	White
EOC	8710163329949

Specifications - PILA BVP007 50W 4000k MDU

Benefits

- Energy saving
- Robust luminaire
- Reliable quality



Product description	PILA BVP007 50W 4000k MDU
Light output (lm)	4250
Power (W)	50
CCT (K)	4000
Mains voltage	220-240V / 50-60Hz
Lifetime	20,000 hrs L70B50
CRI	70
Connection	Flying wire
IP rating	IP65 / IK08
Power factor	> 0.9
Safety class	Class I
Housing material	Polycarbonate/steel
Color	White
EOC	8710163329956

Specifications - PILA BVP007 10W 3000k MDU

Benefits

- Energy saving
- Robust luminaire
- Reliable quality



Product description	PILA BVP007 10W 3000k MDU
Light output (lm)	850
Power (W)	10
CCT (K)	3000
Mains voltage	220-240V / 50-60Hz
Lifetime	20,000 hrs L70B50
CRI	70
Connection	Flying wire
IP rating	IP65 / IK08
Power factor	> 0.9
Safety class	Class I
Housing material	Polycarbonate/steel
Color	White
EOC	8710163329963

Specifications - PILA BVP007 20W 3000k MDU

Benefits

- Energy saving
- Robust luminaire
- Reliable quality



Product description	PILA BVP007 20W 3000k MDU
Light output (lm)	1700
Power (W)	20
CCT (K)	3000
Mains voltage	220-240V / 50-60Hz
Lifetime	20,000 hrs L70B50
CRI	70
Connection	Flying wire
IP rating	IP65 / IK08
Power factor	> 0.9
Safety class	Class I
Housing material	Polycarbonate/steel
Color	White
EOC	8710163329970

Specifications - PILA BVP007 50W 3000k MDU

Benefits

- Energy saving
- Robust luminaire
- Reliable quality



Product description	PILA BVP007 50W 3000k MDU
Light output (lm)	4250
Power (W)	50
CCT (K)	3000
Mains voltage	220-240V / 50-60Hz
Lifetime	20,000 hrs L70B50
CRI	70
Connection	Flying wire
IP rating	IP65 / IK08
Power factor	> 0.9
Safety class	Class I
Housing material	Polycarbonate/steel
Color	White
EOC	8710163329987



PILA
I.B.R.S. / C.C.R.I. Nummer 10461
5600 VB Eindhoven
The Netherlands

www.pilalamps.com